IRONING AND FOLDING

# FLATWORK IRONERS
## ROLLER Ø 500
## PSP-50-200/260/330 TP2

## CHARACTERISTICS

### TP2
- TP2 microprocessor, 7" touch screen, easy to use and fully programmable.
- USB connection. Free online platform for programming, telemetry, data analysis... thanks to IoT.
- 37 languages 5 preset programs.

### EFFICIENCY
- Good heat conduction thanks to the material and thickness of the roll: greater control of energy consumption.
- Automatic switch-off at 80ºC (adjustable parameter).
- Smoke circulation circuit at the bottom to reduce energy consumption.
- Model with radiant burner: 25% more productive.
- Automatic regulation of the ironing speed according to the residual humidity as standard.
- High production system, peed ironing up to 15m/min as standard (not compatible with folder).

### VERSATILITY
- Radiant gas model: flexible, suitable for high altitude installations.
- Optional built-in longitudinal folder with or without rear exit option.

### ROBUSTNESS
- Nomex quality ironing belts: resistant to high temperatures.
- Grey skinplate panels.
- Nickel-plated roller as an option: anti-corrosive, more durable.
- Reinforced mechanical structure.

### ERGONOMICS
- Acoustic comfort : <65 dB
- Suitable working height: 1170 mm feed belts.
- Compact design to save space.

### MAINTENANCE
- Easy access to all components on both sides of the machine.
- Connections : electrical connection and air extraction.
- Complete technical menu: statistics, self-test, data retrieval for technician and maintenance.

### OTHERS
- Dries and irons flat linen from a high spin washer in a single operation.
- Front feed and return.
- Built-in cooling system.
- Polished steel roller ø 500 mm.
- Working widths: 2000, 2600 and 3300 mm.
- Electric, radiant gas or steam heating. CE certified.

## OPTIONS
- Nickel-plated roller (except steam model).
- Propane gas for radiant gas model.
- Natural gas for radiant gas model.
- Longitudinal folder (front outlet).
- Longitudinal folder (front and rear outlet).
- Standard rear outlet (model without folder).
- Antistatic ironing belts without folder.
- Antistatic ironing belts + folder bar.
- Cross folder.
- Hygienic tray to avoid contact between clothes and the floor.
- Wooden maritime packaging.

# TECHNICAL DATA
# FLATWORK IRONERS | ROLLER Ø 500 | PSP-50-200/260/330 TP2

| | | UNIT | PSP-50-200 TP2 | | PSP-50-260 TP2 | | PSP-50-330 TP2 | |
|---|---|---|---|---|---|---|---|---|
| GENERAL DETAILS | | | | | | | | |
| Theorical production (electric heating)* | | Kg/h | 68 | | 84 | | 115 | |
| | | Lb/h | 150 | | 185 | | 254 | |
| Theorical production (gas atmo heating)* | | Kg/h | 68 | | 84 | | 115 | |
| | | Lb/h | 150 | | 185 | | 254 | |
| Theorical production (radiant gas heating)* | | Kg/h | 82 | | 100 | | 138 | |
| | | Lb/h | 181 | | 220 | | 304 | |
| Theorical production (steam heating)* | | Kg/h | 68 | | 84 | | 115 | |
| | | Lb/h | 150 | | 185 | | 254 | |
| Roll Ø | | mm | 500 | | 500 | | 500 | |
| | | inch | 19,69 | | 19,69 | | 19,69 | |
| Working width | | mm | 2000 | | 2600 | | 3300 | |
| | | inch | 78,74 | | 102,36 | | 129,92 | |
| Heigh floor-feeding belts | | mm | 1170 | | 1170 | | 1170 | |
| | | inch | 46,06 | | 46,06 | | 46,06 | |
| Working speed | | m/min | 0,5-8 | | 0,5-8 | | 0,5-8 | |
| | | ft/min | 1,6-26 | | 1,6-26 | | 1,6-26 | |
| Electronic control | | | Yes | | Yes | | Yes | |
| Nº Programs | | Nº | 5 | | 5 | | 5 | |
| Rear exit without folding | | | Opt. | | Opt. | | Opt. | |
| Lenght folder - Front exit | | | Opt. | | Opt. | | Opt. | |
| Lenght folder - Rear exit | | | Opt. | | Opt. | | Opt. | |
| Hygienic tray | | | Opt. | | Opt. | | Opt. | |
| Large surface contact with linen | | | 305 | | 305 | | 305 | |
| POWER | | | | | | | | |
| Electric | Heating power | kW | 31,5 | | 40,5 | | 54 | |
| | Total electric power | kW | 32,16 | | 41,41 | | 54,91 | |
| Gas | Heating power | kW | 40 | | 55 | | 69 | |
| | Total electric power | kW | 0,62 | | 0,87 | | 0,87 | |
| Steam | Heating power | kW | 50 | | 64 | | 81 | |
| | Total electric power | kW | 0,62 | | 0,87 | | 0,87 | |
| | Steam consuption | Kg/h | 50 | | 67 | | 85 | |
| Roll motor power | | kW | 0,41 | | 0,41 | | 0,41 | |
| Fan motor power | | kW | 0,25 | | 0,25 x 2 | | 0,25 x 2 | |
| CONNECTIONS | | | ELECTRIC | STEAM/ GAS | ELECTRIC | STEAM/ GAS | ELECTRIC | STEAM/ GAS |
| Tension 230V - I + N + T | | nº x mm²/A | N/A | 3 x 2,5 / 10A | N/A | 3 x 2,5 / 10A | N/A | 3 x 2,5 / 10A |
| | | n° x AWG/A | N/A | 3 x 13 / 10A | N/A | 3 x 13 / 10A | N/A | 3 x 13 / 10A |
| Tension 230V - III + T | | nº x mm²/A | 4 x 25 /100A | 4 x 2,5 / 10A | 4 x 25 /125A | 4 x 2,5 / 10A | 4 x 35 /160A | 4 x 2,5 / 10A |
| | | n° x AWG/A | 4 x 3 / 100A | 4 x 13 / 10A | 4 x 3 / 125A | 4 x 13 / 10A | 4 x 2 / 160A | 4 x 13 / 10A |
| Tension 400V - III + N + T | | nº x mm²/A | 5 x 16 / 63A | 5 x 2,5 / 10A | 5 x 16 / 80A | 5 x 2,5 / 10A | 5 x 25 /100A | 5 x 2,5 / 10A |
| | | n° x AWG/A | 5 x 5 / 63A | 5 x 13 / 10A | 5 x 5 / 80A | 5 x 13 / 10A | 5 x 3 / 100A | 5 x 13 / 10A |
| Ø Gas inlet | | BSP | 1" | | 1" | | 1" | |
| Ø Steam inlet | | BSP | 3/4" | | 3/4" | | 3/4" | |
| Ø Condensed (Steam models) | | BSP | 1/2" | | 1/2" | | 1/2" | |
| DIMENSIONS / DIMENSIONS WITH PACKAGING | | | | | | | | |
| Net width / Gross width | | mm | 3110 / 3290 | | 3710 / 3890 | | 4410 / 4590 | |
| | | inch | 122,4 / 129,5 | | 146,1 / 153,1 | | 173,6 / 180,7 | |
| Net depth / Gross depth | | mm | 1175 / 1360 | | 1175 / 1360 | | 1175 / 1360 | |
| | | inch | 46,3 / 53,5 | | 46,3 / 53,5 | | 46,3 / 53,5 | |
| Net height / Gross height | | mm | 1780 / 1940 | | 1780 / 1940 | | 1780 / 1940 | |
| | | inch | 70,1 / 76,4 | | 70,1 / 76,4 | | 70,1 / 76,4 | |
| Net weight / Gross weight | | Kg | 1130 / 1190 | | 1380 / 1460 | | 1630 / 1730 | |
| | | Lb | 2491 / 2624 | | 3042 / 3219 | | 3594 / 3814 | |
| Volume | | m3 | 6,50 / 8,68 | | 7,76 / 10,26 | | 9,22 / 12,11 | |
| | | f3 | 230 / 307 | | 274 / 362 | | 326 / 428 | |

*45 % moisture

| OTHERS | | | | |
|---|---|---|---|---|
| No. Fume outlet | Nº | 1 | 2 | 2 |
| Ø Fume outlet | mm | 153 | 153 | 153 |
| | inch | 6,0 | 6,0 | 6,0 |
| Air flow | m3/h | 600 | 1200 | 1200 |
| | cfm | 353 | 706 | 706 |
| Noise level | dB | 65 | 65 | 65 |
| Evaporation power | l/h | 37 | 45 | 62 |
| | USgallon/h | 9,7 | 11,9 | 16,4 |
| Additional ELECTRIC POWER for opt. STD rear exit | kW | 0,13 | 0,13 | 0,13 |
| Additional ELECTRIC POWER for opt. folder front exit option | kW | 0,23 | 0,23 | 0,23 |
| Additional ELECTRIC POWER for folder rear exit option | kW | 0,1 | 0,1 | 0,1 |
| Additional ELECTRIC POWER for folder front + rear exit option | kW | 0,33 | 0,33 | 0,33 |

01. Control panel
02. Steam outlet ø1/2".
03. Gas inlet ø22 or steam inlet ø3/4" 04.
04. Power supply
05. ø152 steam extraction
06. Disconnector

| | A | B | C | D | E | F | G | H | I | J |
|---|---|---|---|---|---|---|---|---|---|---|
| PSP-50-200 TP2 | 3110 | 1729 | 1584 | 1445 | 1313 | 1130 | 1729 | 1428 | 1553 | 1101 |
| PSP-50-260 TP2 | 3710 | 1729 | 1584 | 1445 | 1313 | 1130 | 1729 | 1428 | 1553 | 1101 |
| PSP-50-330 TP2 | 4410 | 1729 | 1584 | 1445 | 1313 | 1130 | 1729 | 1428 | 1553 | 1101 |

This machine must be installed on a perfectly level floor.
This machine can be placed against a wall, but for ease of maintenance, it is best to leave a 1500mm space.

IRONING AND FOLDING

# FLATWORK IRONERS
## ROLLER Ø 500
## PSP-50-200/260/330 TP2

**STD RE**

## CHARACTERISTICS

### TP2
- TP2 microprocessor, 7" touch screen, easy to use and fully programmable.
- USB connection. Free online platform for programming, telemetry, data analysis... thanks to IoT.
- 37 languages 5 preset programs.

### EFFICIENCY
- Good heat conduction thanks to the material and thickness of the roll: greater control of energy consumption.
- Automatic switch-off at 80ºC (adjustable parameter).
- Smoke circulation circuit at the bottom to reduce energy consumption.
- Model with radiant burner: 25% more productive.
- Automatic regulation of the ironing speed according to the residual humidity as standard.
- High production system, ironing up to 15m/min as standard (not compatible with folder).

### VERSATILITY
- Radiant gas model: flexible, suitable for high altitude installations.
- Optional built-in longitudinal folder with or without rear exit option.

### ROBUSTNESS
- Nomex quality ironing belts: resistant to high temperatures.
- Grey skinplate panels.
- Nickel-plated roller as an option: anti-corrosive, more durable.
- Reinforced mechanical structure.

### ERGONOMICS
- Acoustic comfort : <65 dB
- Suitable working height: 1170 mm feed belts.
- Compact design to save space.

### MAINTENANCE
- Easy access to all components on both sides of the machine.
- Connections : electrical connection and air extraction.
- Complete technical menu: statistics, self-test, data retrieval for technician and maintenance.

### OTHERS
- Dries and irons flat linen from a high spin washer in a single operation.
- Front feed and return.
- Built-in cooling system.
- Polished steel roller ø 500 mm.
- Working widths: 2000, 2600 and 3300 mm.
- Electric, radiant gas or steam heating. CE certified.

## OPTIONS
- Nickel-plated roller (except steam model).
- Propane gas for radiant gas model.
- Natural gas for radiant gas model.
- Longitudinal folder (front outlet).
- Longitudinal folder (front and rear outlet).
- Standard rear outlet (model without folder).
- Antistatic ironing belts without folder.
- Antistatic ironing belts + folder bar.
- Cross folder.
- Hygienic tray to avoid contact between clothes and the floor.
- Wooden maritime packaging.

# TECHNICAL DATA
# FLATWORK IRONERS | ROLLER Ø 500 | PSP-50-200/260/330 TP2

| | | UNIT | PSP-50-200 TP2 | | PSP-50-260 TP2 | | PSP-50-330 TP2 | |
|---|---|---|---|---|---|---|---|---|
| GENERAL DETAILS | | | | | | | | |
| Theorical production (electric heating)* | | Kg/h | 68 | | 84 | | 115 | |
| | | Lb/h | 150 | | 185 | | 254 | |
| Theorical production (gas atmo heating)* | | Kg/h | 68 | | 84 | | 115 | |
| | | Lb/h | 150 | | 185 | | 254 | |
| Theorical production (radiant gas heating)* | | Kg/h | 82 | | 100 | | 138 | |
| | | Lb/h | 181 | | 220 | | 304 | |
| Theorical production (steam heating)* | | Kg/h | 68 | | 84 | | 115 | |
| | | Lb/h | 150 | | 185 | | 254 | |
| Roll Ø | | mm | 500 | | 500 | | 500 | |
| | | inch | 19,69 | | 19,69 | | 19,69 | |
| Working width | | mm | 2000 | | 2600 | | 3300 | |
| | | inch | 78,74 | | 102,36 | | 129,92 | |
| Heigh floor-feeding belts | | mm | 1170 | | 1170 | | 1170 | |
| | | inch | 46,06 | | 46,06 | | 46,06 | |
| Working speed | | m/min | 0,5-8 | | 0,5-8 | | 0,5-8 | |
| | | ft/min | 1,6-26 | | 1,6-26 | | 1,6-26 | |
| Electronic control | | | Yes | | Yes | | Yes | |
| Nº Programs | | Nº | 5 | | 5 | | 5 | |
| Rear exit without folding | | | Yes | | Yes | | Yes | |
| Lenght folder - Front exit | | | Opt. | | Opt. | | Opt. | |
| Lenght folder - Rear exit | | | Opt. | | Opt. | | Opt. | |
| Hygienic tray | | | Opt. | | Opt. | | Opt. | |
| Large surface contact with linen | | | 305 | | 305 | | 305 | |
| POWER | | | | | | | | |
| Electric | Heating power | kW | 31,5 | | 40,5 | | 54 | |
| | Total electric power | kW | 32,29 | | 41,41 | | 55,04 | |
| Gas | Heating power | kW | 40 | | 55 | | 69 | |
| | Total electric power | kW | 0,75 | | 1 | | 1 | |
| Steam | Heating power | kW | 50 | | 64 | | 81 | |
| | Total electric power | kW | 0,75 | | 1 | | 1 | |
| | Steam consuption | Kg/h | 50 | | 67 | | 85 | |
| Roll motor power | | kW | 0,41 | | 0,41 | | 0,41 | |
| Fan motor power | | kW | 0,25 | | 0,25 x 2 | | 0,25 x 2 | |
| CONNECTIONS | | | ELECTRIC | STEAM/ GAS | ELECTRIC | STEAM/ GAS | ELECTRIC | STEAM/ GAS |
| Tension 230V - I + N + T | | nº x mm²/A | N/A | 3 x 2,5 / 10A | N/A | 3 x 2,5 / 10A | N/A | 3 x 2,5 / 10A |
| | | n° x AWG/A | N/A | 3 x 13 / 10A | N/A | 3 x 13 / 10A | N/A | 3 x 13 / 10A |
| Tension 230V - III + T | | nº x mm²/A | 4 x 25 /100A | 4 x 2,5 / 10A | 4 x 25 /125A | 4 x 2,5 / 10A | 4 x 35 /160A | 4 x 2,5 / 10A |
| | | n° x AWG/A | 4 x 3 / 100A | 4 x 13 / 10A | 4 x 3 / 125A | 4 x 13 / 10A | 4 x 2 / 160A | 4 x 13 / 10A |
| Tension 400V - III + N + T | | nº x mm²/A | 5 x 16 / 63A | 5 x 2,5 / 10A | 5 x 16 / 80A | 5 x 2,5 / 10A | 5 x 25 /100A | 5 x 2,5 / 10A |
| | | n° x AWG/A | 5 x 5 / 63A | 5 x 13 / 10A | 5 x 5 / 80A | 5 x 13 / 10A | 5 x 3 / 100A | 5 x 13 / 10A |
| Ø Gas inlet | | BSP | 1" | | 1" | | 1" | |
| Ø Steam inlet | | BSP | 3/4" | | 3/4" | | 3/4" | |
| Ø Condensed (Steam models) | | BSP | 1/2" | | 1/2" | | 1/2" | |
| DIMENSIONS / DIMENSIONS WITH PACKAGING | | | | | | | | |
| Net width / Gross width | | mm | 3110 / 3290 | | 3710 / 3890 | | 4410 / 4590 | |
| | | inch | 122,4 / 129,5 | | 146,1 / 153,1 | | 173,6 / 180,7 | |
| Net depth / Gross depth | | mm | 1175 / 1360 | | 1175 / 1360 | | 1175 / 1360 | |
| | | inch | 46,3 / 53,5 | | ***46,3 / 53,5*** | | 46,3 / 53,5 | |
| Net height / Gross height | | mm | 1780 / 1940 | | 1780 / 1940 | | 1780 / 1940 | |
| | | inch | 70,1 / 76,4 | | 70,1 / 76,4 | | 70,1 / 76,4 | |
| Net weight / Gross weight | | Kg | 1160 / 1220 | | 1420 / 1500 | | 1680 / 1780 | |
| | | Lb | 2557 / 2690 | | 3131 / 3307 | | 3704 / 3924 | |
| Volume | | m3 | 6,50 / 8,68 | | 7,76 / 10,26 | | 9,22 / 12,11 | |
| | | f3 | 230 / 307 | | 274 / 362 | | 326 / 428 | |

*45 % moisture

| OTHERS | | | | |
|---|---|---|---|---|
| No. Fume outlet | Nº | 1 | 2 | 2 |
| Ø Fume outlet | mm | 153 | 153 | 153 |
| | inch | 6,0 | 6,0 | 6,0 |
| Air flow | m3/h | 600 | 1200 | 1200 |
| | cfm | 353 | 706 | 706 |
| Noise Level | dB | 65 | 65 | 65 |
| Evaporation powe | l/h | 37 | 45 | 62 |
| | USgallon/h | 9,7 | 11,9 | 16,4 |
| Additional ELECTRIC POWER for opt. STD rear exit | kW | 0,13 | 0,13 | 0,13 |
| Additional ELECTRIC POWER for opt. folder front exit option | kW | 0,23 | 0,23 | 0,23 |
| Additional ELECTRIC POWER for folder rear exit option | kW | 0,1 | 0,1 | 0,1 |
| Additional ELECTRIC POWER for folder front + rear exit option | kW | 0,33 | 0,33 | 0,33 |

01. Control panel
02. Steam outlet ø1/2".
03. Gas inlet ø22 or steam inlet ø3/4" 04.
04. Power supply
05. ø152 steam extraction
06. Disconnector

| | A | B | C | D | E | F | G | H | I | J |
|---|---|---|---|---|---|---|---|---|---|---|
| PSP-50-200 TP2 | 3110 | 1729 | 1584 | 1445 | 1313 | 1130 | 1729 | 1428 | 1553 | 1101 |
| PSP-50-260 TP2 | 3710 | 1729 | 1584 | 1445 | 1313 | 1130 | 1729 | 1428 | 1553 | 1101 |
| PSP-50-330 TP2 | 4410 | 1729 | 1584 | 1445 | 1313 | 1130 | 1729 | 1428 | 1553 | 1101 |

This machine must be installed on a perfectly level floor.
This machine can be placed against a wall, but for ease of maintenance, it is best to leave a 1500mm space.

IRONING AND FOLDING

# FLATWORK IRONERS
## ROLLER Ø 500
## PSP-50-200/260/330 TP2

## FOLDER FE

## CHARACTERISTICS

### TP2
- TP2 microprocessor, 7" touch screen, easy to use and fully programmable.
- USB connection. Free online platform for programming, telemetry, data analysis... thanks to IoT.
- 37 languages 5 preset programs.

### EFFICIENCY
- Good heat conduction thanks to the material and thickness of the roll: greater control of energy consumption.
- Automatic switch-off at 80ºC (adjustable parameter).
- Smoke circulation circuit at the bottom to reduce energy consumption.
- Model with radiant burner: 25% more productive.
- Automatic regulation of the ironing speed according to the residual humidity as standard.
- High production system, speed ironing up to 15m/min as standard (not compatible with folder).

### VERSATILITY
- Radiant gas model: flexible, suitable for high altitude installations.
- Optional built-in longitudinal folder with or without rear exit option.

### ROBUSTNESS
- Nomex quality ironing belts: resistant to high temperatures.
- Grey skinplate panels.
- Nickel-plated roller as an option: anti-corrosive, more durable.
- Reinforced mechanical structure.

### ERGONOMICS
- Acoustic comfort : <65 dB
- Suitable working height: 1170 mm feed belts.
- Compact design to save space.

### MAINTENANCE
- Easy access to all components on both sides of the machine.
- Connections : electrical connection and air extraction.
- Complete technical menu: statistics, self-test, data retrieval for technician and maintenance.

### OTHERS
- Dries and irons flat linen from a high spin washer in a single operation.
- Front feed and return.
- Built-in cooling system.
- Polished steel roller ø 500 mm.
- Working widths: 2000, 2600 and 3300 mm.
- Electric, radiant gas or steam heating. CE certified.

## OPTIONS
- Nickel-plated roller (except steam model).
- Propane gas for radiant gas model.
- Natural gas for radiant gas model.
- Longitudinal folder (front outlet).
- Longitudinal folder (front and rear outlet).
- Standard rear outlet (model without folder).
- Antistatic ironing belts without folder.
- Antistatic ironing belts + folder bar.
- Cross folder.
- Hygienic tray to avoid contact between clothes and the floor.
- Wooden maritime packaging.

# TECHNICAL DATA
# FLATWORK IRONERS | ROLLER Ø 500 | PSP-50-200/260/330 TP2

| | | UNIT | PSP-50-200 TP2 | | PSP-50-260 TP2 | | PSP-50-330 TP2 | |
|---|---|---|---|---|---|---|---|---|
| GENERAL DETAILS | | | | | | | | |
| Theorical production (electric heating)* | | Kg/h | 48 | | 59 | | 81 | |
| | | Lb/h | 105 | | 130 | | 177 | |
| Theorical production (gas atmo heating)* | | Kg/h | 48 | | 59 | | 81 | |
| | | Lb/h | 105 | | 130 | | 177 | |
| Theorical production (radiant gas heating)* | | Kg/h | 57 | | 70 | | 97 | |
| | | Lb/h | 127 | | 154 | | 213 | |
| Theorical production (steam heating)* | | Kg/h | 48 | | 59 | | 81 | |
| | | Lb/h | 105 | | 130 | | 177 | |
| Roll Ø | | mm | 500 | | 500 | | 500 | |
| | | inch | 19,69 | | 19,69 | | 19,69 | |
| Working width | | mm | 2000 | | 2600 | | 3300 | |
| | | inch | 78,74 | | 102,36 | | 129,92 | |
| Heigh floor-feeding belts | | mm | 1170 | | 1170 | | 1170 | |
| | | inch | 46,06 | | 46,06 | | 46,06 | |
| Working speed | | m/min | 2 - 8 | | 2 - 8 | | 2 - 8 | |
| | | ft/min | 6,5 - 26 | | 6,5 - 26 | | 6,5 - 26 | |
| Electronic control | | | Yes | | Yes | | Yes | |
| Nº Programs | | Nº | 5 | | 5 | | 5 | |
| Rear exit without folding | | | No | | No | | No | |
| Lenght folder - Front exit | | | Yes | | Yes | | Yes | |
| Lenght folder - Rear exit | | | No | | No | | No | |
| Hygienic tray | | | Opt. | | Opt. | | Opt. | |
| Large surface contact with linen | | | 305 | | 305 | | 305 | |
| POWER | | | | | | | | |
| Electric | Heating power | kW | 31,5 | | 40,5 | | 54 | |
| | Total electric power | kW | 32,39 | | 41,64 | | 55,14 | |
| Gas | Heating power | kW | 40 | | 55 | | 69 | |
| | Total electric power | kW | 0,88 | | 1,13 | | 1,13 | |
| Steam | Heating power | kW | 50 | | 64 | | 81 | |
| | Total electric power | kW | 0,88 | | 1,13 | | 1,13 | |
| | Steam consuption | Kg/h | 50 | | 67 | | 85 | |
| Roll motor power | | kW | 0,41 | | 0,41 | | 0,41 | |
| Fan motor power | | kW | 0,25 | | 0,25 x 2 | | 0,25 x 2 | |
| CONNECTIONS | | | ELECTRIC | STEAM/ GAS | ELECTRIC | STEAM/ GAS | ELECTRIC | STEAM/ GAS |
| Tension 230V - I + N + T | | nº x mm²/A | N/A | 3 x 2,5 / 10A | N/A | 3 x 2,5 / 10A | N/A | 3 x 2,5 / 10A |
| | | n° x AWG/A | N/A | 3 x 13 / 10A | N/A | 3 x 13 / 10A | N/A | 3 x 13 / 10A |
| Tension 230V - III + T | | nº x mm²/A | 4 x 25 /100A | 4 x 2,5 / 10A | 4 x 25 /125A | 4 x 2,5 / 10A | 4 x 35 /160A | 4 x 2,5 / 10A |
| | | n° x AWG/A | 4 x 3 / 100A | 4 x 13 / 10A | 4 x 3 / 125A | 4 x 13 / 10A | 4 x 2 / 160A | 4 x 13 / 10A |
| Tension 400V - III + N + T | | nº x mm²/A | 5 x 16 / 63A | 5 x 2,5 / 10A | 5 x 16 / 80A | 5 x 2,5 / 10A | 5 x 25 /100A | 5 x 2,5 / 10A |
| | | n° x AWG/A | 5 x 5 / 63A | 5 x 13 / 10A | 5 x 5 / 80A | 5 x 13 / 10A | 5 x 3 / 100A | 5 x 13 / 10A |
| Ø Gas inlet | | BSP | 1" | | 1" | | 1" | |
| Ø Steam inlet | | BSP | 3/4" | | 3/4" | | 3/4" | |
| Ø Condensed (Steam models) | | BSP | 1/2" | | 1/2" | | 1/2" | |
| DIMENSIONS / DIMENSIONS WITH PACKAGING | | | | | | | | |
| Net width / Gross width | | mm | 3110 / 3290 | | 3710 / 3890 | | 4410 / 4590 | |
| | | inch | 122,4 / 129,5 | | 146,1 / 153,1 | | 173,6 / 180,7 | |
| Net depth / Gross depth | | mm | 1175 / 1360 | | 1175 / 1360 | | 1175 / 1360 | |
| | | inch | 46,3 / 53,5 | | 46,3 / 53,5 | | 46,3 / 53,5 | |
| Net height / Gross height | | mm | 1780 / 1940 | | 1780 / 1940 | | 1780 / 1940 | |
| | | inch | 70,1 / 76,4 | | 70,1 / 76,4 | | 70,1 / 76,4 | |
| Net weight / Gross weight | | Kg | 1190 / 1475 | | 1475 / 1555 | | 1760 / 1860 | |
| | | Lb | 2734 / 3384 | | 3384 / 3428 | | 4057 / 4101 | |
| Volume | | m3 | 6,50 / 8,68 | | 7,76 / 10,26 | | 9,22 / 12,11 | |
| | | f3 | 230 / 307 | | 274 / 362 | | 326 / 428 | |

*45 % moisture

| OTHERS | | | | |
|---|---|---|---|---|
| No. Fume outlet | Nº | 1 | 2 | 2 |
| Ø Fume outlet | mm | 153 | 153 | 153 |
| | inch | 6,0 | 6,0 | 6,0 |
| Air flow | m3/h | 600 | 1200 | 1200 |
| | cfm | 353 | 706 | 706 |
| Noise Level | dB | 65 | 65 | 65 |
| Evaporation powe | l/h | 26 | 32 | 43 |
| | USgallon/h | 6,8 | 8,3 | 11,5 |
| Additional ELECTRIC POWER for opt. STD rear exit | kW | 0,13 | 0,13 | 0,13 |
| Additional ELECTRIC POWER for opt. folder front exit option | kW | 0,23 | 0,23 | 0,23 |
| Additional ELECTRIC POWER for folder rear exit option | kW | 0,1 | 0,1 | 0,1 |
| Additional ELECTRIC POWER for folder front + rear exit option | kW | 0,33 | 0,33 | 0,33 |

01. Control panel
02. Steam outlet ø1/2".
03. Gas inlet ø22 or steam inlet ø3/4" 04.
04. Power supply
05. ø152 steam extraction
06. Disconnector

| | A | B | C | D | E | F | G | H | I | J |
|---|---|---|---|---|---|---|---|---|---|---|
| PSP-50-200 TP2 | 3110 | 1729 | 1584 | 1445 | 1313 | 1130 | 1729 | 1428 | 1553 | 1101 |
| PSP-50-260 TP2 | 3710 | 1729 | 1584 | 1445 | 1313 | 1130 | 1729 | 1428 | 1553 | 1101 |
| PSP-50-330 TP2 | 4410 | 1729 | 1584 | 1445 | 1313 | 1130 | 1729 | 1428 | 1553 | 1101 |

This machine must be installed on a perfectly level floor.
This machine can be placed against a wall, but for ease of maintenance, it is best to leave a 1500mm space.

IRONING AND FOLDING

# FLATWORK IRONERS
## ROLLER Ø 500
## PSP-50-200/260/330 TP2

## FOLDER FE RE

## CHARACTERISTICS

### TP2
- TP2 microprocessor, 7" touch screen, easy to use and fully programmable.
- USB connection. Free online platform for programming, telemetry, data analysis... thanks to IoT.
- 37 languages 5 preset programs.

### EFFICIENCY
- Good heat conduction thanks to the material and thickness of the roll: greater control of energy consumption.
- Automatic switch-off at 80ºC (adjustable parameter).
- Smoke circulation circuit at the bottom to reduce energy consumption.
- Model with radiant burner: 25% more productive.
- Automatic regulation of the ironing speed according to the residual humidity as standard.
- High production system, speed ironing up to 15m/min as standard (not compatible with folder).

### VERSATILITY
- Radiant gas model: flexible, suitable for high altitude installations.
- Optional built-in longitudinal folder with or without rear exit option.

### ROBUSTNESS
- Nomex quality ironing belts: resistant to high temperatures.
- Grey skinplate panels.
- Nickel-plated roller as an option: anti-corrosive, more durable.
- Reinforced mechanical structure.

### ERGONOMICS
- Acoustic comfort : <65 dB
- Suitable working height: 1170 mm feed belts.
- Compact design to save space.

### MAINTENANCE
- Easy access to all components on both sides of the machine.
- Connections : electrical connection and air extraction.
- Complete technical menu: statistics, self-test, data retrieval for technician and maintenance.

### OTHERS
- Dries and irons flat linen from a high spin washer in a single operation.
- Front feed and return.
- Built-in cooling system.
- Polished steel roller ø 500 mm.
- Working widths: 2000, 2600 and 3300 mm.
- Electric, radiant gas or steam heating. CE certified.

## OPTIONS
- Nickel-plated roller (except steam model).
- Propane gas for radiant gas model.
- Natural gas for radiant gas model.
- Longitudinal folder (front outlet).
- Longitudinal folder (front and rear outlet).
- Standard rear outlet (model without folder).
- Antistatic ironing belts without folder.
- Antistatic ironing belts + folder bar.
- Cross folder.
- Hygienic tray to avoid contact between clothes and the floor.
- Wooden maritime packaging.

# TECHNICAL DATA
# FLATWORK IRONERS | ROLLER Ø 500 | PSP-50-200/260/330 TP2

| | | UNIT | PSP-50-200 TP2 | | PSP-50-260 TP2 | | PSP-50-330 TP2 | |
|---|---|---|---|---|---|---|---|---|
| GENERAL DETAILS | | | | | | | | |
| Theorical production (electric heating)* | | Kg/h | 44 | | 55 | | 75 | |
| | | Lb/h | 97 | | 120 | | 165 | |
| Theorical production (gas atmo heating)* | | Kg/h | 44 | | 55 | | 75 | |
| | | Lb/h | 97 | | 120 | | 165 | |
| Theorical production (radiant gas heating)* | | Kg/h | 53 | | 65 | | 90 | |
| | | Lb/h | 118 | | 143 | | 198 | |
| Theorical production (steam heating)* | | Kg/h | 44 | | 55 | | 75 | |
| | | Lb/h | 97 | | 120 | | 165 | |
| Roll Ø | | mm | 500 | | 500 | | 500 | |
| | | inch | 19,69 | | 19,69 | | 19,69 | |
| Working width | | mm | 2000 | | 2600 | | 3300 | |
| | | inch | 78,74 | | 102,36 | | 129,92 | |
| Heigh floor-feeding belts | | mm | 1170 | | 1170 | | 1170 | |
| | | inch | 46,06 | | 46,06 | | 46,06 | |
| Working speed | | m/min | 2 - 8 | | 2 - 8 | | 2 - 8 | |
| | | ft/min | 6,5 - 26 | | 6,5 - 26 | | 6,5 - 26 | |
| Electronic control | | | Yes | | Yes | | Yes | |
| Nº Programs | | Nº | 5 | | 5 | | 5 | |
| Rear exit without folding | | | No | | No | | No | |
| Lenght folder - Front exit | | | Yes | | Yes | | Yes | |
| Lenght folder - Rear exit | | | Yes | | Yes | | Yes | |
| Hygienic tray | | | Opt. | | Opt. | | Opt. | |
| Large surface contact with linen | | | 305 | | 305 | | 305 | |
| POWER | | | | | | | | |
| Electric | Heating power | kW | 31,5 | | 40,5 | | 54 | |
| | Total electric power | kW | 32,49 | | 41,74 | | 55,24 | |
| Gas | Heating power | kW | 40 | | 55 | | 69 | |
| | Total electric power | kW | 1,01 | | 1,26 | | 1,26 | |
| Steam | Heating power | kW | 50 | | 64 | | 81 | |
| | Total electric power | kW | 1,01 | | 1,26 | | 1,26 | |
| | Steam consuption | Kg/h | 50 | | 67 | | 85 | |
| Roll motor power | | kW | 0,41 | | 0,41 | | 0,41 | |
| Fan motor power | | kW | 0,25 | | 0,25 x 2 | | 0,25 x 2 | |
| CONNECTIONS | | | ELECTRIC | STEAM/ GAS | ELECTRIC | STEAM/ GAS | ELECTRIC | STEAM/ GAS |
| Tension 230V - I + N + T | | nº x mm²/A | N/A | 3 x 2,5 / 10A | N/A | 3 x 2,5 / 10A | N/A | 3 x 2,5 / 10A |
| | | n° x AWG/A | N/A | 3 x 13 / 10A | N/A | 3 x 13 / 10A | N/A | 3 x 13 / 10A |
| Tension 230V - III + T | | nº x mm²/A | 4 x 25 /100A | 4 x 2,5 / 10A | 4 x 25 /125A | 4 x 2,5 / 10A | 4 x 35 /160A | 4 x 2,5 / 10A |
| | | n° x AWG/A | 4 x 3 / 100A | 4 x 13 / 10A | 4 x 3 / 125A | 4 x 13 / 10A | 4 x 2 / 160A | 4 x 13 / 10A |
| Tension 400V - III + N + T | | nº x mm²/A | 5 x 16 / 63A | 5 x 2,5 / 10A | 5 x 16 / 80A | 5 x 2,5 / 10A | 5 x 25 /100A | 5 x 2,5 / 10A |
| | | n° x AWG/A | 5 x 5 / 63A | 5 x 13 / 10A | 5 x 5 / 80A | 5 x 13 / 10A | 5 x 3 / 100A | 5 x 13 / 10A |
| Ø Gas inlet | | BSP | 1" | | 1" | | 1" | |
| Ø Steam inlet | | BSP | 3/4" | | 3/4" | | 3/4" | |
| Ø Condensed (Steam models) | | BSP | 1/2" | | 1/2" | | 1/2" | |
| DIMENSIONS / DIMENSIONS WITH PACKAGING | | | | | | | | |
| Net width / Gross width | | mm | 3110 / 3290 | | 3710 / 3890 | | 4410 / 4590 | |
| | | inch | 122,4 / 129,5 | | 146,1 / 153,1 | | 173,6 / 180,7 | |
| Net depth / Gross depth | | mm | 1175 (1480) / 1360 | | 1175 (1480) / 1360 | | 1175 (1480) / 1360 | |
| | | inch | 46,3 (55,2) / 53,5 | | 46,3 (55,2) / 53,5 | | 46,3 (55,2) / 53,5 | |
| Net height / Gross height | | mm | 1780 / 1940 | | 1780 / 1940 | | 1780 / 1940 | |
| | | inch | 70,1 / 76,4 | | 70,1 / 76,4 | | 70,1 / 76,4 | |
| Net weight / Gross weight | | Kg | 1240 / 1300 | | 1535 / 1615 | | 1840 / 1940 | |
| | | Lb | 2734 / 3866 | | 3384 / 3560 | | 4057 / 4277 | |
| Volume | | m3 | 6,50 (7,99) / 8,68 | | 7,76 (9.53) / 10,26 | | 9,22 (11,32) / 12,11 | |
| | | f3 | 230 (282) / 307 | | 274 (336)/ 362 | | 326 (400) / 428 | |

*45 % moisture

| OTHERS | | | | |
|---|---|---|---|---|
| No. Fume outlet | Nº | 1 | 2 | 2 |
| Ø Fume outlet | mm | 153 | 153 | 153 |
| | inch | 6,0 | 6,0 | 6,0 |
| Air flow | m3/h | 600 | 1200 | 1200 |
| | cfm | 353 | 706 | 706 |
| Noise Level | dB | 65 | 65 | 65 |
| Evaporation powe | l/h | 24 | 29 | 40 |
| | USgallon/h | 6,3 | 7,7 | 10,7 |
| Additional ELECTRIC POWER for opt. STD rear exit | kW | 0,13 | 0,13 | 0,13 |
| Additional ELECTRIC POWER for opt. folder front exit option | kW | 0,23 | 0,23 | 0,23 |
| Additional ELECTRIC POWER for folder rear exit option | kW | 0,1 | 0,1 | 0,1 |
| Additional ELECTRIC POWER for folder front + rear exit option | kW | 0,33 | 0,33 | 0,33 |

01. Control panel
02. Steam outlet ø1/2".
03. Gas inlet ø22 or steam inlet ø3/4" 04.
04. Power supply
05. ø152 steam extraction
06. Disconnector

| | A | B | C | D | E | F | G | H | I | J |
|---|---|---|---|---|---|---|---|---|---|---|
| PSP-50-200 TP2 | 3110 | 1729 | 1584 | 1445 | 1313 | 1130 | 1729 | 1428 | 1553 | 1101 |
| PSP-50-260 TP2 | 3710 | 1729 | 1584 | 1445 | 1313 | 1130 | 1729 | 1428 | 1553 | 1101 |
| PSP-50-330 TP2 | 4410 | 1729 | 1584 | 1445 | 1313 | 1130 | 1729 | 1428 | 1553 | 1101 |

This machine must be installed on a perfectly level floor.
This machine can be placed against a wall, but for ease of maintenance, it is best to leave a 1500mm space.

IRONING AND FOLDING

# FLATWORK IRONERS
## ROLLER Ø 650
## PSP-65-200/260/330 TP2

## CHARACTERISTICS

### TP2
- TP2 microprocessor, 7" touch screen, easy to use and fully programmable.
- USB connection.Free online platform for programming, telemetry, data analysis... thanks to IoT.
- 37 languages 5 preset programs.

### EFFICIENCY
- Good heat conduction thanks to the material and thickness of the roll: greater control of energy consumption.
- Automatic switch-off at 80ºC (adjustable parameter).
- Smoke circulation circuit at the bottom to reduce energy consumption.
- Model with radiant burner: 25% more productive.
- Automatic regulation of the ironing speed according to the residual humidity as standard.
- High production system, speed ironing up to 15m/min as standard (not compatible with folder).

### VERSATILITY
- Radiant gas model: flexible, suitable for high altitude installations.
- Optional built-in longitudinal folder with or without rear exit option.

### ROBUSTNESS
- Nomex quality ironing belts: resistant to high temperatures.
- Grey skinplate panels.
- Nickel-plated roller as an option: anti-corrosive, more durable.
- Reinforced mechanical structure.

### ERGONOMICS
- Acoustic comfort : <65 dB
- Suitable working height: 1170 mm feed belts.
- Compact design to save space.

### MAINTENANCE
- Easy access to all components on both sides of the machine.
- Connections : electrical connection and air extraction.
- Complete technical menu: statistics, self-test, data retrieval for technician and maintenance.

### OTHERS
- Dries and irons flat linen from a high spin washer in a single operation.
- Front feed and return.
- Built-in cooling system.
- Polished steel roller ø 650 mm.
- Working widths: 2000, 2600 and 3300 mm.
- Electric, radiant gas or steam heating. CE certified.

## OPTIONS
- Nickel-plated roller (except steam model).
- Propane gas for radiant gas model.
- Natural gas for radiant gas model.
- Longitudinal folder (front outlet).
- Longitudinal folder (front and rear outlet).
- Standard rear outlet (model without folder).
- Antistatic ironing belts without folder.
- Antistatic ironing belts + folder bar.
- Cross folder.
- Hygienic tray to avoid contact between clothes and the floor.
- Wooden maritime packaging.

# TECHNICAL DATA
# FLATWORK IRONERS | ROLLER Ø 650 | PSP-65-200/260/330 TP2

| | | UNIT | PSP-65-200 TP2 | | PSP-65-260 TP2 | | PSP-65-330 TP2 | |
|---|---|---|---|---|---|---|---|---|
| GENERAL DETAILS | | | | | | | | |
| Theorical production (electric heating)* | | Kg/h | 90 | | 115 | | 160 | |
| | | Lb/h | 198 | | 254 | | 353 | |
| Theorical production (gas atmo heating)* | | Kg/h | - | | - | | - | |
| | | Lb/h | N/A | | N/A | | N/A | |
| Theorical production (radiant gas heating)* | | Kg/h | 104 | | 132 | | 184 | |
| | | Lb/h | 229 | | 291 | | 406 | |
| Theorical production (steam heating)* | | Kg/h | 78 | | 115 | | 132 | |
| | | Lb/h | 172 | | 254 | | 291 | |
| Roll Ø | | mm | 650 | | 650 | | 650 | |
| | | inch | 25,59 | | 25,59 | | 25,59 | |
| Working width | | mm | 2000 | | 2600 | | 3300 | |
| | | inch | 78,74 | | 102,36 | | 129,92 | |
| Heigh floor-feeding belts | | mm | 1170 | | 1170 | | 1170 | |
| | | inch | 46,06 | | 46,06 | | 46,06 | |
| Working speed | | m/min | 0,5-15 | | 0,5-15 | | 0,5-15 | |
| | | ft/min | 1.6-49 | | 1.6-49 | | 1.6-49 | |
| Electronic control | | | Yes | | Yes | | Yes | |
| Nº Programs | | Nº | 5 | | 5 | | 5 | |
| Rear exit without folding | | | Opt. | | Opt. | | Opt. | |
| Lenght folder - Front exit | | | Opt. | | Opt. | | Opt. | |
| Lenght folder - Rear exit | | | Opt. | | Opt. | | Opt. | |
| Hygienic tray | | | Opt. | | Opt. | | Opt. | |
| Large surface contact with linen | | | 305 | | 305 | | 305 | |
| POWER | | | | | | | | |
| Electric | Heating power | kW | 42 | | 54 | | 72 | |
| | Total electric power | kW | 43,05 | | 55,05 | | 73,05 | |
| Gas | Heating power | kW | 52 | | 69 | | 78 | |
| | Total electric power | kW | 1,05 | | 1,05 | | 1,05 | |
| Steam | Heating power | kW | 60 | | 76 | | 97 | |
| | Total electric power | kW | 1,05 | | 1,05 | | 1,05 | |
| | Steam consuption | Kg/h | 60 | | 80 | | 102 | |
| Roll motor power | | kW | 0,55 | | 0,55 | | 0,55 | |
| Fan motor power | | kW | 0,25 x 2 | | 0,25 x 2 | | 0,25 x 2 | |
| CONNECTIONS | | | ELECTRIC | STEAM/ GAS | ELECTRIC | STEAM/ GAS | ELECTRIC | STEAM/ GAS |
| Tension 230V - I + N + T | | nº x mm²/A | N/A | 3 x 2,5 / 10A | N/A | 3 x 2,5 / 10A | N/A | 3 x 2,5 / 10A |
| | | n° x AWG/A | N/A | 3 x 13 / 10A | N/A | 3 x 13 / 10A | N/A | 3 x 13 / 10A |
| Tension 230V - III + T | | nº x mm²/A | 4 x 25 /125A | 4 x 2,5 / 10A | 4 x 35 /160A | 4 x 2,5 / 10A | N/A | 4 x 2,5 / 10A |
| | | n° x AWG/A | 4 x 3 / 125A | 4 x 13 / 10A | 4 x 2 / 160A | 4 x 13 / 10A | N/A | 4 x 13 / 10A |
| Tension 400V - III + N + T | | nº x mm²/A | 5 x 16 / 80A | 5 x 2,5 / 10A | 5 x 25 /100A | 5 x 2,5 / 10A | 5 x 25 /125A | 5 x 2,5 / 10A |
| | | n° x AWG/A | 5 x 5 / 80A | 5 x 13 / 10A | 5 x 3 /100A | 5 x 13 / 10A | 5 x 3 / 125A | 5 x 13 / 10A |
| Ø Gas inlet | | BSP | 1/2" | | 1/2" | | 1/2" | |
| Ø Steam inlet | | BSP | 3/4" | | 3/4" | | 3/4" | |
| Ø Condensed (Steam models) | | BSP | 1/2" | | 1/2" | | 1/2" | |
| DIMENSIONS / DIMENSIONS WITH PACKAGING | | | | | | | | |
| Net width / Gross width | | mm | 3110 / 3290 | | 3710 / 3890 | | 4410 / 4590 | |
| | | inch | 122,4 / 129,5 | | 146,1 / 153,1 | | 173,6 / 180,7 | |
| Net depth / Gross depth | | mm | 1175 / 1360 | | 1175 / 1360 | | 1175 / 1360 | |
| | | inch | 46,3 / 53,5 | | 46,3 / 53,5 | | 46,3 / 53,5 | |
| Net height / Gross height | | mm | 1780 / 1940 | | 1780 / 1940 | | 1780 / 1940 | |
| | | inch | 70,1 / 76,4 | | 70,1 / 76,4 | | 70,1 / 76,4 | |
| Net weight / Gross weight | | Kg | 1389 / 1449 | | 1717 / 1797 | | 1965 / 2065 | |
| | | Lb | 3062 / 3194 | | 3785 / 3962 | | 4332 / 4553 | |
| Volume | | m3 | 6,50 / 8,68 | | 7,76 / 10,26 | | 9,22 / 12,11 | |
| | | f3 | 230 / 307 | | 274 / 362 | | 326 / 428 | |

*45 % moisture

| OTHERS | | | | |
|---|---|---|---|---|
| No. Fume outlet | Nº | 2 | 2 | 2 |
| Ø Fume outlet | mm | 153 | 153 | 153 |
| | inch | 6,0 | 6,0 | 6,0 |
| Air flow | m3/h | 1200 | 1200 | 1200 |
| | cfm | 706 | 706 | 706 |
| Noise level | dB | 65 | 65 | 65 |
| Evaporation power | l/h | 47 | 59 | 83 |
| | USgallon/h | 12,4 | 15,7 | 21,9 |
| Additional ELECTRIC POWER for opt. STD rear exit | kW | 0,13 | 0,13 | 0,13 |
| Additional ELECTRIC POWER for opt. folder front exit option | kW | 0,23 | 0,23 | 0,23 |
| Additional ELECTRIC POWER for folder rear exit option | kW | 0,1 | 0,1 | 0,1 |
| Additional ELECTRIC POWER for folder front + rear exit option | kW | 0,33 | 0,33 | 0,33 |

01. Control panel
02. Steam outlet ø1/2".
03. Gas inlet ø22 or steam inlet ø3/4" 04.
04. Power supply
05. ø152 steam extraction
06. Disconnector

| | A | B | C | D | E | F | G | H | I | J |
|---|---|---|---|---|---|---|---|---|---|---|
| PSP-65-200 TP2 | 3110 | 1729 | 1584 | 1445 | 1313 | 1130 | 1729 | 1428 | 1553 | 1101 |
| PSP-65-260 TP2 | 3710 | 1729 | 1584 | 1445 | 1313 | 1130 | 1729 | 1428 | 1553 | 1101 |
| PSP-65-330 TP2 | 4410 | 1729 | 1584 | 1445 | 1313 | 1130 | 1729 | 1428 | 1553 | 1101 |

This machine must be installed on a perfectly level floor.
This machine can be placed against a wall, but for ease of maintenance, it is best to leave a 1500mm space.

IRONING AND FOLDING

# FLATWORK IRONERS
## ROLLER Ø 650
## PSP-65-200/260/330 TP2

**STD RE**

## CHARACTERISTICS

### TP2
- TP2 microprocessor, 7" touch screen, easy to use and fully programmable.
- USB connection. Free online platform for programming, telemetry, data analysis... thanks to IoT.
- 37 languages 5 preset programs.

### EFFICIENCY
- Good heat conduction thanks to the material and thickness of the roll: greater control of energy consumption.
- Automatic switch-off at 80ºC (adjustable parameter).
- Smoke circulation circuit at the bottom to reduce energy consumption.
- Model with radiant burner: 25% more productive.
- Automatic regulation of the ironing speed according to the residual humidity as standard.
- High production system, speed ironing up to 15m/min as standard (not compatible with folder).

### VERSATILITY
- Radiant gas model: flexible, suitable for high altitude installations.
- Optional built-in longitudinal folder with or without rear exit option.

### ROBUSTNESS
- Nomex quality ironing belts: resistant to high temperatures.
- Grey skinplate panels.
- Nickel-plated roller as an option: anti-corrosive, more durable.
- Reinforced mechanical structure.

### ERGONOMICS
- Acoustic comfort : <65 dB
- Suitable working height: 1170 mm feed belts.
- Compact design to save space.

### MAINTENANCE
- Easy access to all components on both sides of the machine.
- Connections : electrical connection and air extraction.
- Complete technical menu: statistics, self-test, data retrieval for technician and maintenance.

### OTHERS
- Dries and irons flat linen from a high spin washer in a single operation.
- Front feed and return.
- Built-in cooling system.
- Polished steel roller ø 650 mm.
- Working widths: 2000, 2600 and 3300 mm.
- Electric, radiant gas or steam heating.
- CE certified.

## OPTIONS
- Nickel-plated roller (except steam model).
- Propane gas for radiant gas model.
- Natural gas for radiant gas model.
- Longitudinal folder (front outlet).
- Longitudinal folder (front and rear outlet).
- Standard rear outlet (model without folder).
- Antistatic ironing belts without folder.
- Antistatic ironing belts + folder bar.
- Cross folder.
- Hygienic tray to avoid contact between clothes and the floor.
- Wooden maritime packaging.

# TECHNICAL DATA
# FLATWORK IRONERS | ROLLER Ø 650 | PSP-65-200/260/330 TP2

| | | UNIT | PSP-65-200 TP2 | | PSP-65-260 TP2 | | PSP-65-330 TP2 | |
|---|---|---|---|---|---|---|---|---|
| GENERAL DETAILS | | | | | | | | |
| Theorical production (electric heating)* | | Kg/h | 90 | | 115 | | 160 | |
| | | Lb/h | 198 | | 254 | | 353 | |
| Theorical production (gas atmo heating)* | | Kg/h | - | | - | | - | |
| | | Lb/h | N/A | | N/A | | N/A | |
| Theorical production (radiant gas heating)* | | Kg/h | 104 | | 132 | | 184 | |
| | | Lb/h | 229 | | 291 | | 406 | |
| Theorical production (steam heating)* | | Kg/h | 78 | | 115 | | 132 | |
| | | Lb/h | 172 | | 254 | | 291 | |
| Roll Ø | | mm | 650 | | 650 | | 650 | |
| | | inch | 25,59 | | 25,59 | | 25,59 | |
| Working width | | mm | 2000 | | 2600 | | 3300 | |
| | | inch | 78,74 | | 102,36 | | 129,92 | |
| Heigh floor-feeding belts | | mm | 1170 | | 1170 | | 1170 | |
| | | inch | 46,06 | | 46,06 | | 46,06 | |
| Working speed | | m/min | 0,5-15 | | 0,5-15 | | 0,5-15 | |
| | | ft/min | 1.6-49 | | 1.6-49 | | 1.6-49 | |
| Electronic control | | | Yes | | Yes | | Yes | |
| Nº Programs | | Nº | 5 | | 5 | | 5 | |
| Rear exit without folding | | | Yes | | Yes | | Yes | |
| Lenght folder - Front exit | | | Opt. | | Opt. | | Opt. | |
| Lenght folder - Rear exit | | | Opt. | | Opt. | | Opt. | |
| Hygienic tray | | | Opt. | | Opt. | | Opt. | |
| Large surface contact with linen | | | 305 | | 305 | | 305 | |
| POWER | | | | | | | | |
| Electric | Heating power | kW | 42 | | 54 | | 72 | |
| | Total electric power | kW | 43,18 | | 55,18 | | 73,18 | |
| Gas | Heating power | kW | 52 | | 69 | | 78 | |
| | Total electric power | kW | 1,18 | | 1,18 | | 1,18 | |
| Steam | Heating power | kW | 60 | | 76 | | 97 | |
| | Total electric power | kW | 1,18 | | 1,18 | | 1,18 | |
| | Steam consuption | Kg/h | 60 | | 80 | | 102 | |
| Roll motor power | | kW | 0,55 | | 0,55 | | 0,55 | |
| Fan motor power | | kW | 0,25 x 2 | | 0,25 x 2 | | 0,25 x 2 | |
| CONNECTIONS | | | ELECTRIC | STEAM/ GAS | ELECTRIC | STEAM/ GAS | ELECTRIC | STEAM/ GAS |
| Tension 230V - I + N + T | | nº x mm²/A | N/A | 3 x 2,5 / 10A | N/A | 3 x 2,5 / 10A | N/A | 3 x 2,5 / 10A |
| | | n° x AWG/A | N/A | 3 x 13 / 10A | N/A | 3 x 13 / 10A | N/A | 3 x 13 / 10A |
| Tension 230V - III + T | | nº x mm²/A | 4 x 25 /125A | 4 x 2,5 / 10A | 4 x 35 /160A | 4 x 2,5 / 10A | N/A | 4 x 2,5 / 10A |
| | | n° x AWG/A | 4 x 3 / 125A | 4 x 13 / 10A | 4 x 2 / 160A | 4 x 13 / 10A | N/A | 4 x 13 / 10A |
| Tension 400V - III + N + T | | nº x mm²/A | 5 x 16 / 80A | 5 x 2,5 / 10A | 5 x 25 /100A | 5 x 2,5 / 10A | 5 x 25 /125A | 5 x 2,5 / 10A |
| | | n° x AWG/A | 5 x 5 / 80A | 5 x 13 / 10A | 5 x 3 /100A | 5 x 13 / 10A | 5 x 3 / 125A | 5 x 13 / 10A |
| Ø Gas inlet | | BSP | 1/2" | | 1/2" | | 1/2" | |
| Ø Steam inlet | | BSP | 3/4" | | 3/4" | | 3/4" | |
| Ø Condensed (Steam models) | | BSP | 1/2" | | 1/2" | | 1/2" | |
| DIMENSIONS / DIMENSIONS WITH PACKAGING | | | | | | | | |
| Net width / Gross width | | mm | 3110 / 3290 | | 3710 / 3890 | | 4410 / 4590 | |
| | | inch | 122,4 / 129,5 | | 146,1 / 153,1 | | 173,6 / 180,7 | |
| Net depth / Gross depth | | mm | 1175 / 1360 | | 1175 / 1360 | | 1175 / 1360 | |
| | | inch | 46,3 / 53,5 | | 46,3 / 53,5 | | 46,3 / 53,5 | |
| Net height / Gross height | | mm | 1780 / 1940 | | 1780 / 1940 | | 1780 / 1940 | |
| | | inch | 70,1 / 76,4 | | 70,1 / 76,4 | | 70,1 / 76,4 | |
| Net weight / Gross weight | | Kg | 1419 / 1479 | | 1757 / 1837 | | 2015 / 2115 | |
| | | Lb | 3128 / 3261 | | 3874 / 4050 | | 4442 / 4663 | |
| Volume | | m3 | 6,50 / 8,68 | | 7,76 / 10,26 | | 9,22 / 12,11 | |
| | | f3 | 230 / 307 | | 274 / 362 | | 326 / 428 | |

*45 % moisture

| OTHERS | | | | |
|---|---|---|---|---|
| No. Fume outlet | Nº | 2 | 2 | 2 |
| Ø Fume outlet | mm | 153 | 153 | 153 |
| | inch | 6,0 | 6,0 | 6,0 |
| Air flow | m3/h | 1200 | 1200 | 1200 |
| | cfm | 706 | 706 | 706 |
| Noise level | dB | 65 | 65 | 65 |
| Evaporation power | l/h | 47 | 59 | 83 |
| | USgallon/h | 12,4 | 15,7 | 21,9 |
| Additional ELECTRIC POWER for opt. STD rear exit | kW | 0,13 | 0,13 | 0,13 |
| Additional ELECTRIC POWER for opt. folder front exit option | kW | 0,23 | 0,23 | 0,23 |
| Additional ELECTRIC POWER for folder rear exit option | kW | 0,1 | 0,1 | 0,1 |
| Additional ELECTRIC POWER for folder front + rear exit option | kW | 0,33 | 0,33 | 0,33 |

01. Control panel
02. Steam outlet ø1/2".
03. Gas inlet ø22 or steam inlet ø3/4" 04.
04. Power supply
05. ø152 steam extraction
06. Disconnector

| | A | B | C | D | E | F | G | H | I | J |
|---|---|---|---|---|---|---|---|---|---|---|
| PSP-65-200 TP2 | 3110 | 1729 | 1584 | 1445 | 1313 | 1130 | 1729 | 1428 | 1553 | 1101 |
| PSP-65-260 TP2 | 3710 | 1729 | 1584 | 1445 | 1313 | 1130 | 1729 | 1428 | 1553 | 1101 |
| PSP-65-330 TP2 | 4410 | 1729 | 1584 | 1445 | 1313 | 1130 | 1729 | 1428 | 1553 | 1101 |

This machine must be installed on a perfectly level floor.
This machine can be placed against a wall, but for ease of maintenance, it is best to leave a 1500mm space.

IRONING AND FOLDING

# FLATWORK IRONERS
## ROLLER Ø 650
## PSP-65-200/260/330 TP2

## FOLDER FE

## CHARACTERISTICS

### TP2
- TP2 microprocessor, 7" touch screen, easy to use and fully programmable.
- USB connection. Free online platform for programming, telemetry, data analysis... thanks to IoT.
- 37 languages 5 preset programs.

### EFFICIENCY
- Good heat conduction thanks to the material and thickness of the roll: greater control of energy consumption.
- Automatic switch-off at 80ºC (adjustable parameter).
- Smoke circulation circuit at the bottom to reduce energy consumption.
- Model with radiant burner: 25% more productive.
- Automatic regulation of the ironing speed according to the residual humidity as standard.
- High production system, speed ironing up to 15m/min as standard (not compatible with folder).

### VERSATILITY
- Radiant gas model: flexible, suitable for high altitude installations.
- Optional built-in longitudinal folder with or without rear exit option.

### ROBUSTNESS
- Nomex quality ironing belts: resistant to high temperatures.
- Grey skinplate panels.
- Nickel-plated roller as an option: anti-corrosive, more durable.
- Reinforced mechanical structure.

### ERGONOMICS
- Acoustic comfort : <65 dB
- Suitable working height: 1170 mm feed belts.
- Compact design to save space.

### MAINTENANCE
- Easy access to all components on both sides of the machine.
- Connections : electrical connection and air extraction.
- Complete technical menu: statistics, self-test, data retrieval for technician and maintenance.

### OTHERS
- Dries and irons flat linen from a high spin washer in a single operation.
- Front feed and return.
- Built-in cooling system.
- Polished steel roller ø 650 mm.
- Working widths: 2000, 2600 and 3300 mm.
- Electric, radiant gas or steam heating. CE certified.

## OPTIONS
- Nickel-plated roller (except steam model).
- Propane gas for radiant gas model.
- Natural gas for radiant gas model.
- Longitudinal folder (front outlet).
- Longitudinal folder (front and rear outlet).
- Standard rear outlet (model without folder).
- Antistatic ironing belts without folder.
- Antistatic ironing belts + folder bar.
- Cross folder.
- Hygienic tray to avoid contact between clothes and the floor.
- Wooden maritime packaging.

# TECHNICAL DATA
# FLATWORK IRONERS | ROLLER Ø 650 | PSP-65-200/260/330 TP2

| | | UNIT | PSP-65-200 TP2 | | PSP-65-260 TP2 | | PSP-65-330 TP2 | |
|---|---|---|---|---|---|---|---|---|
| GENERAL DETAILS | | | | | | | | |
| Theorical production (electric heating)* | | Kg/h | 63 | | 81 | | 112 | |
| | | Lb/h | 139 | | 177 | | 247 | |
| Theorical production (gas atmo heating)* | | Kg/h | - | | - | | - | |
| | | Lb/h | N/A | | N/A | | N/A | |
| Theorical production (radiant gas heating)* | | Kg/h | 73 | | 92 | | 129 | |
| | | Lb/h | 160 | | 204 | | 284 | |
| Theorical production (steam heating)* | | Kg/h | 55 | | 81 | | 92 | |
| | | Lb/h | 120 | | 177 | | 204 | |
| Roll Ø | | mm | 650 | | 650 | | 650 | |
| | | inch | 25,59 | | 25,59 | | 25,59 | |
| Working width | | mm | 2000 | | 2600 | | 3300 | |
| | | inch | 78,74 | | 102,36 | | 129,92 | |
| Heigh floor-feeding belts | | mm | 1170 | | 1170 | | 1170 | |
| | | inch | 46,06 | | 46,06 | | 46,06 | |
| Working speed | | m/min | 2 - 10 | | 2 - 10 | | 2 - 10 | |
| | | ft/min | 6,5 - 32 | | 6,5 - 32 | | 6,5 - 32 | |
| Electronic control | | | Yes | | Yes | | Yes | |
| Nº Programs | | Nº | 5 | | 5 | | 5 | |
| Rear exit without folding | | | No | | No | | No | |
| Lenght folder - Front exit | | | Yes | | Yes | | Yes | |
| Lenght folder - Rear exit | | | No | | No | | No | |
| Hygienic tray | | | Opt. | | Opt. | | Opt. | |
| Large surface contact with linen | | | 305 | | 305 | | 305 | |
| POWER | | | | | | | | |
| Electric | Heating power | kW | 42 | | 54 | | 72 | |
| | Total electric power | kW | 43,28 | | 55,28 | | 73,28 | |
| Gas | Heating power | kW | 52 | | 69 | | 78 | |
| | Total electric power | kW | 1,31 | | 1,31 | | 1,31 | |
| Steam | Heating power | kW | 60 | | 76 | | 97 | |
| | Total electric power | kW | 1,31 | | 1,31 | | 1,31 | |
| | Steam consuption | Kg/h | 60 | | 80 | | 102 | |
| Roll motor power | | kW | 0,55 | | 0,55 | | 0,55 | |
| Fan motor power | | kW | 0,25 x 2 | | 0,25 x 2 | | 0,25 x 2 | |
| CONNECTIONS | | | ELECTRIC | STEAM/ GAS | ELECTRIC | STEAM/ GAS | ELECTRIC | STEAM/ GAS |
| Tension 230V - I + N + T | | nº x mm²/A | N/A | 3 x 2,5 / 10A | N/A | 3 x 2,5 / 10A | N/A | 3 x 2,5 / 10A |
| | | n° x AWG/A | N/A | 3 x 13 / 10A | N/A | 3 x 13 / 10A | N/A | 3 x 13 / 10A |
| Tension 230V - III + T | | nº x mm²/A | 4 x 25 /125A | 4 x 2,5 / 10A | 4 x 35 /160A | 4 x 2,5 / 10A | N/A | 4 x 2,5 / 10A |
| | | n° x AWG/A | 4 x 3 / 125A | 4 x 13 / 10A | 4 x 2 / 160A | 4 x 13 / 10A | N/A | 4 x 13 / 10A |
| Tension 400V - III + N + T | | nº x mm²/A | 5 x 16 / 80A | 5 x 2,5 / 10A | 5 x 25 /100A | 5 x 2,5 / 10A | 5 x 25 /125A | 5 x 2,5 / 10A |
| | | n° x AWG/A | 5 x 5 / 80A | 5 x 13 / 10A | 5 x 3 /100A | 5 x 13 / 10A | 5 x 3 / 125A | 5 x 13 / 10A |
| Ø Gas inlet | | BSP | 1/2" | | 1/2" | | 1/2" | |
| Ø Steam inlet | | BSP | 3/4" | | 3/4" | | 3/4" | |
| Ø Condensed (Steam models) | | BSP | 1/2" | | 1/2" | | 1/2" | |
| DIMENSIONS / DIMENSIONS WITH PACKAGING | | | | | | | | |
| Net width / Gross width | | mm | 3110 / 3290 | | 3710 / 3890 | | 4410 / 4590 | |
| | | inch | 122,4 / 129,5 | | 146,1 / 153,1 | | 173,6 / 180,7 | |
| Net depth / Gross depth | | mm | 1175 / 1360 | | 1175 / 1360 | | 1175 / 1360 | |
| | | inch | 46,3 / 53,5 | | 46,3 / 53,5 | | 46,3 / 53,5 | |
| Net height / Gross height | | mm | 1780 / 1940 | | 1780 / 1940 | | 1780 / 1940 | |
| | | inch | 70,1 / 76,4 | | 70,1 / 76,4 | | 70,1 / 76,4 | |
| Net weight / Gross weight | | Kg | 1697 / 1757 | | 1812 / 1892 | | 2095 / 2195 | |
| | | Lb | 3305 / 3874 | | 4127 / 4171 | | 4795 / 4839 | |
| Volume | | m3 | 6,50 / 8,68 | | 7,76 / 10,26 | | 9,22 / 12,11 | |
| | | f3 | 230 / 307 | | 274 / 362 | | 326 / 428 | |

*45 % moisture

| OTHERS | | | | |
|---|---|---|---|---|
| No. Fume outlet | Nº | 2 | 2 | 2 |
| Ø Fume outlet | mm | 153 | 153 | 153 |
| | inch | 6,0 | 6,0 | 6,0 |
| Air flow | m3/h | 1200 | 1200 | 1200 |
| | cfm | 706 | 706 | 706 |
| Noise level | dB | 65 | 65 | 65 |
| Evaporation power | l/h | 33 | 42 | 58 |
| | USgallon/h | 8,7 | 11 | 15,3 |
| Additional ELECTRIC POWER for opt. STD rear exit | kW | 0,13 | 0,13 | 0,13 |
| Additional ELECTRIC POWER for opt. folder front exit option | kW | 0,23 | 0,23 | 0,23 |
| Additional ELECTRIC POWER for folder rear exit option | kW | 0,1 | 0,1 | 0,1 |
| Additional ELECTRIC POWER for folder front + rear exit option | kW | 0,33 | 0,33 | 0,33 |

01. Control panel
02. Steam outlet ø1/2".
03. Gas inlet ø22 or steam inlet ø3/4" 04.
04. Power supply
05. ø152 steam extraction
06. Disconnector

| | A | B | C | D | E | F | G | H | I | J |
|---|---|---|---|---|---|---|---|---|---|---|
| PSP-65-200 TP2 | 3110 | 1729 | 1584 | 1445 | 1313 | 1130 | 1729 | 1428 | 1553 | 1101 |
| PSP-65-260 TP2 | 3710 | 1729 | 1584 | 1445 | 1313 | 1130 | 1729 | 1428 | 1553 | 1101 |
| PSP-65-330 TP2 | 4410 | 1729 | 1584 | 1445 | 1313 | 1130 | 1729 | 1428 | 1553 | 1101 |

This machine must be installed on a perfectly level floor.
This machine can be placed against a wall, but for ease of maintenance, it is best to leave a 1500mm space.

IRONING AND FOLDING

# FLATWORK IRONERS
## ROLLER Ø 650
## PSP-65-200/260/330 TP2

## FOLDER FE RE

## CHARACTERISTICS

### TP2
- TP2 microprocessor, 7" touch screen, easy to use and fully programmable.
- USB connection. Free online platform for programming, telemetry, data analysis... thanks to IoT.
- 37 languages 5 preset programs.

### EFFICIENCY
- Good heat conduction thanks to the material and thickness of the roll: greater control of energy consumption.
- Automatic switch-off at 80ºC (adjustable parameter).
- Smoke circulation circuit at the bottom to reduce energy consumption.
- Model with radiant burner: 25% more productive.
- Automatic regulation of the ironing speed according to the residual humidity as standard.
- High production system, speed ironing up to 15m/min as standard (not compatible with folder).

### VERSATILITY
- Radiant gas model: flexible, suitable for high altitude installations.
- Optional built-in longitudinal folder with or without rear exit option.

### ROBUSTNESS
- Nomex quality ironing belts: resistant to high temperatures.
- Grey skinplate panels.
- Nickel-plated roller as an option: anti-corrosive, more durable.
- Reinforced mechanical structure.

### ERGONOMICS
- Acoustic comfort : <65 dB
- Suitable working height: 1170 mm feed belts.
- Compact design to save space.

### MAINTENANCE
- Easy access to all components on both sides of the machine.
- Connections : electrical connection and air extraction.
- Complete technical menu: statistics, self-test, data retrieval for technician and maintenance.

### OTHERS
- Dries and irons flat linen from a high spin washer in a single operation.
- Front feed and return.
- Built-in cooling system.
- Polished steel roller ø 650 mm.
- Working widths: 2000, 2600 and 3300 mm.
- Electric, radiant gas or steam heating. CE certified.

## OPTIONS
- Nickel-plated roller (except steam model).
- Propane gas for radiant gas model.
- Natural gas for radiant gas model.
- Longitudinal folder (front outlet).
- Longitudinal folder (front and rear outlet).
- Standard rear outlet (model without folder).
- Antistatic ironing belts without folder.
- Antistatic ironing belts + folder bar.
- Cross folder.
- Hygienic tray to avoid contact between clothes and the floor.
- Wooden maritime packaging.

# TECHNICAL DATA
# FLATWORK IRONERS | ROLLER Ø 650 | PSP-65-200/260/330 TP2

| | | UNIT | PSP-65-200 TP2 | | PSP-65-260 TP2 | | PSP-65-330 TP2 | |
|---|---|---|---|---|---|---|---|---|
| GENERAL DETAILS | | | | | | | | |
| Theorical production (electric heating)* | | Kg/h | 59 | | 75 | | 104 | |
| | | Lb/h | 129 | | 165 | | 229 | |
| Theorical production (gas atmo heating)* | | Kg/h | - | | - | | - | |
| | | Lb/h | N/A | | N/A | | N/A | |
| Theorical production (radiant gas heating)* | | Kg/h | 68 | | 86 | | 120 | |
| | | Lb/h | 149 | | 189 | | 264 | |
| Theorical production (steam heating)* | | Kg/h | 51 | | 75 | | 86 | |
| | | Lb/h | 112 | | 165 | | 189 | |
| Roll Ø | | mm | 650 | | 650 | | 650 | |
| | | inch | 25,59 | | 25,59 | | 25,59 | |
| Working width | | mm | 2000 | | 2600 | | 3300 | |
| | | inch | 78,74 | | 102,36 | | 129,92 | |
| Heigh floor-feeding belts | | mm | 1170 | | 1170 | | 1170 | |
| | | inch | 46,06 | | 46,06 | | 46,06 | |
| Working speed | | m/min | 2 - 10 | | 2 - 10 | | 2 - 10 | |
| | | ft/min | 6,5 - 32 | | 6,5 - 32 | | 6,5 - 32 | |
| Electronic control | | | Yes | | Yes | | Yes | |
| Nº Programs | | Nº | 5 | | 5 | | 5 | |
| Rear exit without folding | | | No | | No | | No | |
| Lenght folder - Front exit | | | Yes | | Yes | | Yes | |
| Lenght folder - Rear exit | | | Yes | | Yes | | Yes | |
| Hygienic tray | | | Opt. | | Opt. | | Opt. | |
| Large surface contact with linen | | | 305 | | 305 | | 305 | |
| POWER | | | | | | | | |
| Electric | Heating power | kW | 42 | | 54 | | 72 | |
| | Total electric power | kW | 43,38 | | 55,38 | | 73,38 | |
| Gas | Heating power | kW | 52 | | 69 | | 78 | |
| | Total electric power | kW | 1,44 | | 1,44 | | 1,44 | |
| Steam | Heating power | kW | 60 | | 76 | | 97 | |
| | Total electric power | kW | 1,44 | | 1,44 | | 1,44 | |
| | Steam consuption | Kg/h | 60 | | 80 | | 102 | |
| Roll motor power | | kW | 0,55 | | 0,55 | | 0,55 | |
| Fan motor power | | kW | 0,25 x 2 | | 0,25 x 2 | | 0,25 x 2 | |
| CONNECTIONS | | | ELECTRIC | STEAM/ GAS | ELECTRIC | STEAM/ GAS | ELECTRIC | STEAM/ GAS |
| Tension 230V - I + N + T | | nº x mm²/A | N/A | 3 x 2,5 / 10A | N/A | 3 x 2,5 / 10A | N/A | 3 x 2,5 / 10A |
| | | n° x AWG/A | N/A | 3 x 13 / 10A | N/A | 3 x 13 / 10A | N/A | 3 x 13 / 10A |
| Tension 230V - III + T | | nº x mm²/A | 4 x 25 /125A | 4 x 2,5 / 10A | 4 x 35 /160A | 4 x 2,5 / 10A | N/A | 4 x 2,5 / 10A |
| | | n° x AWG/A | 4 x 3 / 125A | 4 x 13 / 10A | 4 x 2 / 160A | 4 x 13 / 10A | N/A | 4 x 13 / 10A |
| Tension 400V - III + N + T | | nº x mm²/A | 5 x 16 / 80A | 5 x 2,5 / 10A | 5 x 25 /100A | 5 x 2,5 / 10A | 5 x 25 /125A | 5 x 2,5 / 10A |
| | | n° x AWG/A | 5 x 5 / 80A | 5 x 13 / 10A | 5 x 3 /100A | 5 x 13 / 10A | 5 x 3 / 125A | 5 x 13 / 10A |
| Ø Gas inlet | | BSP | 1/2" | | 1/2" | | 1/2" | |
| Ø Steam inlet | | BSP | 3/4" | | 3/4" | | 3/4" | |
| Ø Condensed (Steam models) | | BSP | 1/2" | | 1/2" | | 1/2" | |
| DIMENSIONS / DIMENSIONS WITH PACKAGING | | | | | | | | |
| Net width / Gross width | | mm | 3110 / 3290 | | 3710 / 3890 | | 4410 / 4590 | |
| | | inch | 122,4 / 129,5 | | 146,1 / 153,1 | | 173,6 / 180,7 | |
| Net depth / Gross depth | | mm | 1175 / 1360 | | 1175 / 1360 | | 1175 / 1360 | |
| | | inch | 46,3 / 53,5 | | 46,3 / 53,5 | | 46,3 / 53,5 | |
| Net height / Gross height | | mm | 1780 / 1940 | | 1780 / 1940 | | 1780 / 1940 | |
| | | inch | 70,1 / 76,4 | | 70,1 / 76,4 | | 70,1 / 76,4 | |
| Net weight / Gross weight | | Kg | 1697 / 1757 | | 1872 / 1952 | | 2175 / 2275 | |
| | | Lb | 3305 / 3874 | | 4127 / 4303 | | 4795 /5016 | |
| Volume | | m3 | 6,50 / 8,68 | | 7,76 / 10,26 | | 9,22 / 12,11 | |
| | | f3 | 230 / 307 | | 274 / 362 | | 326 / 428 | |

*45 % moisture

| OTHERS | | | | |
|---|---|---|---|---|
| No. Fume outlet | Nº | 2 | 2 | 2 |
| Ø Fume outlet | mm | 153 | 153 | 153 |
| | inch | 6,0 | 6,0 | 6,0 |
| Air flow | m3/h | 1200 | 1200 | 1200 |
| | cfm | 706 | 706 | 706 |
| Noise level | dB | 65 | 65 | 65 |
| Evaporation power | l/h | 30 | 39 | 54 |
| | USgallon/h | 8 | 10,2 | 14,2 |
| Additional ELECTRIC POWER for opt. STD rear exit | kW | 0,13 | 0,13 | 0,13 |
| Additional ELECTRIC POWER for opt. folder front exit option | kW | 0,23 | 0,23 | 0,23 |
| Additional ELECTRIC POWER for folder rear exit option | kW | 0,1 | 0,1 | 0,1 |
| Additional ELECTRIC POWER for folder front + rear exit option | kW | 0,33 | 0,33 | 0,33 |

01. Control panel
02. Steam outlet ø1/2".
03. Gas inlet ø22 or steam inlet ø3/4" 04.
04. Power supply
05. ø152 steam extraction
06. Disconnector

| | A | B | C | D | E | F | G | H | I | J |
|---|---|---|---|---|---|---|---|---|---|---|
| PSP-65-200 TP2 | 3110 | 1729 | 1584 | 1445 | 1313 | 1130 | 1729 | 1428 | 1553 | 1101 |
| PSP-65-260 TP2 | 3710 | 1729 | 1584 | 1445 | 1313 | 1130 | 1729 | 1428 | 1553 | 1101 |
| PSP-65-330 TP2 | 4410 | 1729 | 1584 | 1445 | 1313 | 1130 | 1729 | 1428 | 1553 | 1101 |

This machine must be installed on a perfectly level floor.
This machine can be placed against a wall, but for ease of maintenance, it is best to leave a 1500mm space.

# IRONING AND FOLDING

# CROSS FOLDER AND STACKER PL CROSS-2000/2600/3300 TP2

## FEATURES

Independent cross folder with stacker.

- Working width: 2000 - 2600 - 3300 mm.
- Speed 9mt/min.
- 1 crossfold working lanes.
- Crossfolds by air jet and rotating rolls.
- Contror Touch Plus TP2 panel.
- 20 variable programs with PLC.
- Selection chance of side and exit direction of stacker conveyor.
- Transportation belts in cotton.
- Safety alarm for cross-folds obstructions.
- Calculation of partial and total production.
- Totally personalized foldin parameters.
- Stacking chance from 1 to 10.

# TECHNICAL DATA
# CROSS FOLDER AND STACKER | PL CROSS-2000/2600/3300 TP2

| DATOS TÉCNICOS | UNIT. | PL CROSS-2000 | PL CROSS-2600 | PL CROSS-3300 |
|---|---|---|---|---|
| GENERAL DETAILS | | | | |
| Working width | mm | 710 | 2600 | 3300 |
| Ironing speed | mt/min | 9 | 9 | 9 |
| Nº of programmes | Kg/h | 20 | 20 | 20 |
| FOLDING | | | | |
| 1 lane - crossfold | Nº | 1-2-3 | 1-2-3 | 1-2-3 |
| POWER | | | | |
| Power | kW | 1,5 | 1,5 | 1,5 |
| Voltage 400V - III + N + T | Hz | 50Hz // Amp 3,7 | 50Hz // Amp 3,7 | 50Hz // Amp 3,7 |
| Voltage 230V-III + T | Hz | 50Hz // Amp 6,3 | 50Hz // Amp 6,3 | 50Hz // Amp 6,3 |
| FOLDER DIMENSIONS / PACKAGING DIMENSIONS | | | | |
| Net width / gross width | mm | 3.010 / 3.110 | 3.460 / 3.560 | 4.160 / 4.260 |
| Net depth / gross depth | mm | 1.920 / 2.020 | 1.920 / 2.020 | 1.920 / 2.020 |
| Net height / gross depth | mm | 1.240 / 1.340 | 1.240 / 1.340 | 1.240 / 1.340 |
| Net / gross weight | Kg | 1.150 / 1.200 | 1.400 / 1.450 | 1.680 / 1.730 |
| STACKER DIMENSIONS / PACK DIMENSIONS | | | | |
| Net width / gross width | mm | 710 / 810 | 710 / 810 | 710 / 810 |
| Net depth / gross depth | mm | 7100 / 1800 | 1700 / 1800 | 1700 / 1800 |
| Net height / gross depth | mm | 620 / 720 | 620 / 720 | 620 / 720 |
| Net weight / gross weight | Kg | 180 / 210 | 180 / 210 | 180 / 210 |
| OTHERS | | | | |
| Compressed air needed (6,5 bar) | Nl/h | 3500 | 3500 | 3500 |

| | A | B | C | D |
|---|---|---|---|---|
| PL CROSS 2000 | 2000 | 2330 | 3010 | 3720 |
| PL CROSS 2600 | 2600 | 2780 | 3460 | 4170 |
| PL CROSS 3300 | 3300 | 3480 | 4160 | 4870 |